






Low Profile Type

Appearance	Description	Part Number	Height	Length	Width	Impedance Range (Ω) / Inductance Range (μH)	Current Rating Range (mA)	DCR (m Ω)	Packing (per reel)
	Low Profile series	GPS3010FT	1	3	3	1.0 ~ 33	1750 ~ 270	65 ~ 1300	2000/reel
		GPS3012FT	1.2	3	3	1.0 ~ 47	2000 ~ 250	80 ~ 1330	2000/reel
		GPS3015FT	1.5	3	3	1.0 ~ 82	2100 ~ 270	30 ~ 2000	2000/reel
		GPS3020FT	2	3	3	1.2 ~ 100	2400 ~ 260	24 ~ 1800	3000/reel
		GPS4010FT	1	4	4	1.0 ~ 47	1900 ~ 280	90 ~ 1600	3000/reel
		GPS4012FT	1.2	4	4	0.47 ~ 47	3800 ~ 360	42 ~ 1200	3000/reel
		GPS4015FT	1.5	4	4	1.0 ~ 47	3300 ~ 450	35 ~ 1080	3000/reel
		GPS4018FT	1.8	4	4	1.0 ~ 100	4500 ~ 320	30 ~ 1800	3000/reel
	Low Profile series	GPC3010FT	1	3	2.9	1.00 ~ 22	1700 ~ 330	64 ~ 1000	3000/reel
		GPC3012FT	1.2	3	2.9	0.47 ~ 47	2800 ~ 220	32 ~ 1530	3000/reel
		GPC3015FT	1.5	3	2.9	0.68 ~ 47	3400 ~ 260	38 ~ 1680	3000/reel
		GPC3020FT	2	3	2.9	1.00 ~ 68	3600 ~ 200	51 ~ 2240	3000/reel
		GPC4010FT	1	4	3.9	1.00 ~ 47	1400 ~ 250	56 ~ 1230	3000/reel
		GPC4012FT	1.2	4	3.9	0.47 ~ 47	3500 ~ 380	34 ~ 1140	3000/reel
		GPC4012UT	1.2	4	3.9	2.20 ~ 4.7	1800 ~ 1150	90 ~ 180	3000/reel
		GPC4015FT	1.5	4	3.9	1.00 ~ 100	3600 ~ 250	48 ~ 2460	3000/reel
		GPC4018FT	1.8	4	3.9	0.56 ~ 100	5500 ~ 280	41 ~ 2170	3000/reel
		GPC5010FT	1	5	4.9	1.00 ~ 47	1900 ~ 380	59 ~ 1100	3000/reel
		GPC5012FT	1.2	5	4.9	0.47 ~ 47	3500 ~ 350	32 ~ 920	3000/reel
		SGPC5015FT	1.5	5	4.9	1.00 ~ 220	3500 ~ 250	52 ~ 4250	3000/reel
		GPC5020FT	2	5	4.9	0.47 ~ 100	7500 ~ 400	42 ~ 1440	3000/reel

Appearance	Description	Part Number	Height	Length	Width	Impedance Range (Ω) / Inductance	Current Rating Range (mA)	DCR (m Ω)	Packing (per reel)
	Low Profile series	GPI3012	1.2	3	3	1.0 ~ 33	1800 ~ 250	55 ~ 1210	3000/reel
		GPI3015	1.5	3	3	1.0 ~ 27	2200 ~ 400	52 ~ 820	3000/reel
		GPI3020	2	3	3	1.2 ~ 68	2000 ~ 270	58 ~ 1640	3000/reel
		GPI4012	1.2	4	4	0.47 ~ 47	3000 ~ 340	35 ~ 1170	3000/reel
		GPI4015	1.5	4	4	1.0 ~ 100	2300 ~ 270	43 ~ 1730	3000/reel
		GPI4018	1.8	4	4	1.0 ~ 100	2700 ~ 300	41 ~ 1780	3000/reel
		GPI5012	1.2	5	5	1.0 ~ 47	2500 ~ 300	45 ~ 1050	3000/reel
		GPI5015	1.5	5	5	2.7 ~ 22	2000 ~ 720	67 ~ 290	3000/reel
		GPI5020	2	5	5	1.0 ~ 68	3800 ~ 460	43 ~ 650	3000/reel
	Low Profile series	GDS252010D	1.02	2.5	2	10 ~ 22	750 ~ 500	470 ~ 1120	2000/reel
		GDS252012D	1.2	2.5	2	10 ~ 22	850 ~ 560	410 ~ 850	2000/reel
		GDS3010D	1.02	3	3	10 ~ 22	630 ~ 430	350 ~ 750	2000/reel
		GDS3012D	1.2	3	3	10 ~ 22	890 ~ 610	245 ~ 580	2000/reel
		GPS201610D	1.02	2	1.6	0.24 ~ 2.2	4400 ~ 1450	45 ~ 180	2000/reel
		GPS201610E	1	2	1.6	0.24 ~ 2.2	4500 ~ 1700	28 ~ 170	2000/reel
		GPS201610H	1.02	2	1.6	0.47 ~ 22	2700 ~ 380	44 ~ 2000	2000/reel
		GPS201612D	1.2	2	1.6	0.24 ~ 2.2	4800 ~ 1600	33 ~ 186	2000/reel
		GPS252010C	1.02	2.5	2	0.47 ~ 22	2850 ~ 500	30 ~ 830	2000/reel
		GPS252010D	1.02	2.5	2	0.47 ~ 2.2	3200 ~ 1900	42 ~ 169	2000/reel
		GPS252012C	1.2	2.5	2	0.47 ~ 22.0	4000 ~ 560	28 ~ 850	2000/reel
		GPS252012D	1.2	2.5	2	0.47 ~ 2.2	3800 ~ 2000	39 ~ 177	2000/reel
		GPS252012E	1.2	2.5	2	0.24 ~ 2.2	6500 ~ 2300	24 ~ 102	2000/reel
		GPS252012H	1.2	2.5	2	1.00 ~ 22	2240 ~ 550	73 ~ 1200	2000/reel

Appearance	Description	Part Number	Height	Length	Width	Impedance Range (Ω) / Inductance	Current Rating Range (mA)	DCR (m Ω)	Packing (per reel)
	Low Profile series	GPS5012FT	1.2	5	5	0.47 ~ 47	5200 ~ 500	53 ~ 1900	3000/reel
		GPS5014FT	1.4	5	5	0.47 ~ 22	5000 ~ 580	32 ~ 640	3000/reel
		GPS5020FT	2	5	5	0.47 ~ 33	7000 ~ 650	15 ~ 500	3000/reel